



# LightBend™ Mini 1x1, 1x2, 2x2 (Bypass) OptoMechanical Fiberoptic Switch

(Protected by U.S. patent 6823102 and pending patents)

## Product Description

The LB Series miniature fiber optic switch connects optical channels by redirecting incoming optical signals into selected output fibers, in 1x1, 1x2 and 2x2 (bypass) configurations. This is achieved using a patent pending opto-mechanical configuration and activated via an electrical control signal. Latching operation preserves the selected optical path after the drive signal has been removed. The switch has integrated status contacts to provide an electrical readout of switch position. The new material based advanced design significantly reduces moving part position sensitivity, offering unprecedented high stability as well as an unmatched low cost. It is designed for use in reconfigurable OADM, optical cross-connect system and network switching for fault protection applications. Electronic driver is available for this series of switches.

We offer tight-bend-fiber version, which reduces the minimum bending radius from normal 15 mm to 7 mm. This feature enables smaller overall foot print.



## Features

- Unmatched Low Cost
- Low Optical Distortions
- Low Cross Talk
- High Reliability
- Epoxy-Free Optical Path

## Performance Specifications

LB 1x1, 1x2, 2x2 (Bypass) Switch	Min	Typical	Max	Unit
Operation Wavelength	850	1260-1360 and/or	1510-1610	nm
Insertion Loss <sup>1</sup>	-5~+70 °C	0.4	0.7	dB
	-40~+85 °C	0.6	1.0	
Wavelength Dependent Loss	SW <sup>1</sup>		0.15	dB
	DW <sup>2</sup>		0.25	
Temperature Dependent Loss	-5~+70 °C		0.25	dB
	-40~+85 °C		0.4	
Polarization Dependent Loss			0.1	dB
Return Loss	55			dB
Cross Talk	55			dB
Switching Time		3	10	ms
Repeatability			±0.02	dB
Durability	10 <sup>7</sup>			Cycle
Operating Voltage	5	5	7	VDC
Operating Current (Latching/Non-Latching)		30	60	mA
Voltage Pulse Width (Latching)		20		ms
Switching Type		Latching or Non-Latching		
Operating Temperature	-5		+70	°C
	-40		+85	
Optical Power Handling		300	500	mW
Storage Temperature	-40		+85	°C
Package Dimension		36.5L x 12.5W x 8.2H		mm

Note:

1. Exclude connectors.
2. SW: Single window.
3. DW: Dual window.

## Applications

- Channel Blocking
- Configurable Add/Drop
- System Monitoring
- Instrumentation




Revision: 060-13  
07-20-10

15 Cabot Rd, Woburn, MA 01801 Tel: (781) 935-1200 Fax: (781) 935-2040  
www.agiltron.com

# LightBend™ Mini 1x1, 1x2, 2x2 (Bypass) OptoMechanical Fiberoptic Switch

## Mechanical Dimensions (Unit:mm)



## Electrical Driving Requirements

The load is a resistive coil which is activated by applying 5V (draw ~ 40mA). Applying too long pulse for the latching version will heat up the device. Agiltron offers a computer control kit with TTL and RS232 interfaces and Windows™ GUI

### Latching Type

LB Mini 1x2 Switch

Optical Path	Electrical Drive		Status Sensor					
	Pin1	Pin10	Pin5	Pin6	Pin2-3	Pin3-4	Pin7-8	Pin 8-9
Port 1 → Port 2	GND	5V Pulse	N/A	N/A	Close	Open	Open	Close
Port 1 → Port 3	5V Pulse	GND	N/A	N/A	Open	Close	Close	Open

LB Mini 2x2 Bypass Switch

Optical Path	Electrical Drive		Status Sensor					
	Pin1	Pin10	Pin5	Pin6	Pin2-3	Pin3-4	Pin7-8	Pin 8-9
Port 1 → Port 2 Port 4 → Port 3	GND	5V Pulse	N/A	N/A	Close	Open	Open	Close
Port 1 → Port 3	5V Pulse	GND	N/A	N/A	Open	Close	Close	Open

### Non-Latching Type

LB Mini 1x2 Switch

Optical Path	Electrical Drive		Status Sensor					
	Pin1	Pin10	Pin5	Pin6	Pin2-3	Pin3-4	Pin7-8	Pin 8-9
Port 1 → Port 2	No Power		N/A	N/A	Close	Open	Open	Close
Port 1 → Port 3	5V	GND	N/A	N/A	Open	Close	Close	Open

LB Mini 2x2 Bypass Switch

Optical Path	Electrical Drive		Status Sensor					
	Pin1	Pin10	Pin5	Pin6	Pin2-3	Pin3-4	Pin7-8	Pin 8-9
Port 1 → Port 2 Port 4 → Port 3	No Power		N/A	N/A	Close	Open	Open	Close
Port 1 → Port 3	5V	GND	N/A	N/A	Open	Close	Close	Open



