

# Fiber-Fiber™ MxN Fiber Optic Switch Module

(all fiber type, ultra-broadband, bidirectional, latching, M/N up to 300)

(Protected by U.S. patents 7224860, 6757101, 6577430 and pending patents)



DATASHEET

BUY NOW



The Fiber-Fiber Series of optical fiber switch is based on a patent-pending self-groove alignment mechanism without needing AR coating and lenses. It offers unparalleled advantages of very low loss of about 1dB for any array size, low cost, amicable to any fiber core size, and broad wavelength operation from 300nm~2300nm. The latching operation preserves the selected optical path after removing the drive signal. Multimode fiber core size is from 50 to 1000 μm. The switch is bidirectional and can accommodate up to 300 fiber ports. The Fiber-Fiber multimode switches are designed with very short paths between fibers, so signals propagate in practically the same distribution as through uninterrupted multimode fiber, uniquely achieving high modal fidelity. It is available in single and dual channels. The dual channel acts at the same time, design for testing applications.

The switch is controlled by RS232 or USB computer interface with graphic Software. The Labview version is also available.

Lightpath in the device is bidirectional.

The order table includes a list of standard control interfaces. Additionally, we provide a list of commands to assist customer engineers in coding. For those who require it, we offer a code-writing service for customer interfaces at an additional charge.

## Specifications

Parameter	Min	Typical	Max	Unit
Operation Wavelength	400	1260~1650	1800	nm
Insertion Loss <sup>[1]</sup>		1	2.0	dB
Cross Talk	55	60		dB
Extinction Ratio (PM Fiber)	18		23	dB
Switch Speed (Rise, Fall)			1000	ms
Durability	10 <sup>7</sup>			cycle
Polarization Dependent Loss		0.04	0.2	dB
Wavelength Dependence Loss <sup>[2]</sup>		0.1	0.3	dB
Return Loss	45			dB
Repeatability		0.05	0.1	dB
Operation Voltage <sup>[3]</sup>			12	V
Power Consumption <sup>[4]</sup>	0.7	3.6	5	W
Operating Temperature <sup>[5]</sup>	-5		65	°C
Optical Power Handling <sup>[6]</sup>		300	500 <sup>[6]</sup>	mW
Storage Temperature	-40		85	°C
Switch type	Non-Latching/Latching			
Fiber Type	SMF-28 or 50/125μm or 62.5/125μm			
Package Dimension	Connector dependent W/LC=2RU/96 Ports			

### Notes:

- [1]. Measured without connectors for 1xN. For multimode fiber, use a laser source with CPR<15
- [2]. Within 50nm bandwidth
- [3]. Other voltage options also available
- [4]. Consume minimum power during sleep time, latching switch type only
- [5]. -25°C~75°C version is also available.
- [6]. High power version available

## Features

- High Reliability
- Ultra Low Insertion Loss
- Broad Band
- Latching
- All Fiber Types

## Applications

- Optical Signal Routing
- Network Protection
- Wavelength Management
- Signal Monitoring
- Instrumentation

**Legal notices:** All product information is believed to be accurate and is subject to change without notice. Information contained herein shall legally bind Agiltron only if it is specifically incorporated into the terms and conditions of a sales agreement. Some specific combinations of options may not be available. The user assumes all risks and liability whatsoever in connection with the use of a product or its application.

Rev 04/13/24

© Photonwares Corporation

+1 781-935-1200

sales@photonwares.com

www.agiltron.com

Information contained herein is deemed to be reliable and accurate as of the issue date. Photonwares reserves the right to change the design or specifications at any time without notice. Agiltron is a registered trademark of Photonwares Corporation in the U.S. and other countries.

# Fiber-Fiber™ MxN Fiber Optic Switch Module

(all fiber type, ultra-broadband, bidirectional, latching, M/N up to 300)



DATASHEET

## Module Mechanical Dimensions


2RU 19" mount rack typically. The input and output connectors are on the front panel, while the control interface and power supplier are on the rear panel.

\*Product dimensions may change without notice. This is sometimes required for non-standard specifications.

## Control Interface and Power Supply

- RS 232
- Ethernet 10/100 with definable IP address
- USB
- GUI
- 110-220V (0.6 A) Power Input

## Typical Graphic User Interface



# Fiber-Fiber™ MxN Fiber Optic Switch Module

(all fiber type, ultra-broadband, bidirectional, latching, M/N up to 300)



## DATASHEET

### Ordering Information

Prefix	Type	Wavelength	Switch Type	Package	Fiber Type	Power Monitor	Connector
<b>SANM-</b>	16x16 = 1616 24x24 = 2424 32x32 = 3232 48x48 = 4848 64x64 = 6464 80x80 = 8080 96x96 = 9696 128x128 = 1282 144x144 = 1442 192x192 = 1922 250x250 = 2502 Special = 0000	1240-1640 = A 1060 = 1 1310 = 3 1410 = 4 1550 = 5 1310/1550 = 2 650 = 6 780 = 7 850 = 8 Special = 0	Latching = 1 Non-latching = 0	Standard = 1 Special = 0	50/NA.22 = 5 62.5/NA.22 = 6 105/NA.15 = E 200/NA.22 = F 300/NA.22 = G 400/NA.22 = H 600/NA.22 = J 800/NA.22 = K <b>Special = 0</b>	Input = 1 Output = 3 Input/Output = 2 No = 0	None = 1 FC/PC = 2 FC/APC = 3 SC/PC = 4 SC/APC = 5 ST/PC = 6 LC/PC = 7 Duplex LC/PC = 8 Quad LC/PC = 9 LC/APC = A LC/UPC = U Special = 0

RED is Special Order

#### Fiber Core Alignment

Note that the minimum attenuation for these devices depends on excellent core-to-core alignment when the connectors are mated. This is crucial for shorter wavelengths with smaller fiber core diameters that can increase the loss of many decibels above the specification if they are not perfectly aligned. Different vendors' connectors may not mate well with each other, especially for angled APC.

#### Fiber Cleanliness

Fibers with smaller core diameters (<5 μm) must be kept extremely clean, contamination at fiber-fiber interfaces, combined with the high optical power density, can lead to significant optical damage. This type of damage usually requires re-polishing or replacement of the connector.

#### Maximum Optical Input Power

Due to their small fiber core diameters for short wavelength and high photon energies, the damage thresholds for device is substantially reduced than the common 1550nm fiber. To avoid damage to the exposed fiber end faces and internal components, the optical input power should never exceed 20 mW for wavelengths shorter 650nm. We produce a special version to increase the handling by expanding the core side at the fiber ends.

# Fiber-Fiber™ MxN Fiber Optic Switch Module

(all fiber type, ultra-broadband, bidirectional, latching, M/N up to 300)



DATASHEET |

## Questions and Answers

**Q:** If the device were to fail, would the switch continue to pass the fiber light through the switch as configured before failure? When power is restored, does the IN/OUT configuration before failure remain in place?

**A:** This depends, if one mirror fails, it only affects the light go through that mirror. Yes, when power back up it will go to the previous points

**Q:** When power is restored, does the IN/OUT configuration before failure remain in place?

**A:** Yes, when power back up it will go to the previous flightpath

**Q:** If power to the device were shutoff, would the device continue to pass the fiber light as configured before failure?

**A:** This function is call latching. We uniquely offer MEMS latching switch but cost more.

**Q:** With the Ethernet Control Option, does the switch support SNMPv3

**A:** Yes. This internet standard protocol allows user to write their own control code

**Q:** With the Ethernet Control Option, what type of encryption does the SNMPv3 use?

**A:** MD5/DES

**Q:** With the Ethernet Control Option, could this device be controlled by multiple users at different locations and all users will also see the configuration updates?

**A:** Yes

**Q:** With the Ethernet Control Option, could this switch be controlled by multiple users at different locations and all users will also see the configuration updates?

**A:** Yes

**Q:** With the Ethernet Control Option, does the user need to install any software on their computer other than a web browser?

**A:** No