

# CrystaLatch™ 1x5 PM High Power Reflection Switch (For Sensor and LIDAR applications)

(Protected by U.S. patents 7224860, 6757101, 6577430 and pending patents)

## Product Description

The CL Series 1x5 PM High Power reflection switch connects optical channels by redirecting an incoming optical signal into a selected output fiber at the same time collect the reflected signal into a dedicate sensor port. This proprietary configuration is designed for sensor and LIDAR application, minimizing optical loss and eliminating the need for additional circulator or coupler. The switching is achieved using patented non-mechanical configurations and activated via an electrical control signal. Latching operation preserves the selected optical path after the drive signal has been removed.

Agiltron non-mechanical CL fiberoptic switch features low insertion loss, fast response time, high extinction ratio, and extremely high reliability and repeatability. It is designed to meet the most demanding switching requirements of continuous operation without wear-out, longevity without fail, and live operation under vibration/shock, as well as -40 C operation. Electronic driver is available for this series of switches.

## Performance Specifications

CL 1X5 PM HP Reflection Switch	Min	Typical	Max	Unit
Operation Wavelength <sup>1</sup>	1520	1550	1580	nm
	1295	1310	1325	nm
Insertion Loss <sup>2</sup>		1.2	1.6	dB
Cross Talk	40	50		dB
Directivity <sup>3</sup>	50	55		dB
Extinction Ratio	20	25		dB
Return Loss <sup>2</sup>	50	55		dB
Reliability	10 <sup>9</sup>			Cycles
Switch Speed (rise, fall)	5	50	200	µs
Repetition Rate		2K		Hz
Durability	10 <sup>11</sup>			cycle
Operating Temperature <sup>4</sup>	0		70	°C
Optical Power Handling <sup>5</sup>			5 <sup>6</sup>	W
Storage Temperature	-40		85	°C
Package Dimension	72L x 37W x 7.8H			mm

1. Agiltron can achieve same SPEC at L band.
2. Measured without connectors.
3. Defined as the optical power at the sensor port when light is launched into the input.
4. -40 C and 85°C version is available as special.
5. High pulse power version is available as special.
6. Continuous operation, for pulse operation call.

## Features

- Solid-State High Speed
- Non-Mechanical
- Ultra-High Reliability
- Fail-Safe Latching
- Low Insertion Loss
- Direct Low Voltage Drive
- Compact
- Vibration Tolerance
- Low Cost

## Applications

- Sensor
- Lidar
- Instrumentation

